

# EIS-LCD 200 / 1000

GSM Door Entry Unit



## FEATURES

- Simple installation and setup
- Back lit for easy visibility
- Up to 200 or 1000\* apartments \*(by model)
- 2 phone numbers per apartment
- Easy access: Up to 1000 additional caller ID numbers and 2000 (4 digit) PIN codes
- 2 relay outputs / 2 alarm inputs
- Up to 20,000 log events
- Supports 3G-GSM wireless carrier



## SPECIFICATIONS

Mounting	Post or Surface
Format	Wiegand 26-bit input / output
Power supply	14.4/24 VDC 12-16 VAC
Current Consumption	
Transmitting Mode	330mA / 14 VDC
Idle Mode	360mA / 14VDC
QUAD Band GSM Module	850/900/1800/1900 MHz
FIVE Band UMTS Module	800/850/1900/2100
Unit Dimensions	11-7/16 x 4-7/16 x 2-3/16"
External Patch Antenna SMA	1
Front Plate	Grade 304 Stainless steel
Lockable Housing	Powder coated

## ACCESSORIES



Programming Software

Available on IOS or Android App and online at [www.eisware.com](http://www.eisware.com).



Search:  
**EISWARE WEB**



Optional receiver and transmitter module for wireless application



2480 South 3850 West, Suite B  
Salt Lake City, UT 84120  
(866) 975-0101 • (866) 975-0404 fax  
[www.transmittersolutions.com](http://www.transmittersolutions.com)

All items are trademarks of their respective holders.

To have your fax number removed from future specials, please call Removal Services - 800-915-2571 ext. 47540 or fax to 866-975-0404.