HEADQUARTERS

ITALY

FAAC SpA
Via Calari 10 - 40069 Zola Predosa (BO)
Tel. +39 051 61724 - Fax +39 051 758518
it.info@faacgroup.com - www.faacgroup.com

SUBSIDIARIES

AUSTRALIA

FAAC AUSTRALIA PTY LTD Homebush — Sydney, Australia tel. +61 2 87565644 fax +61 2 87565677 www.faac.com.au

AUSTRIA

FAAC GMBH Salzburg, Austria tel. +43 662 8533950 fax +43 662 85339525 www.faac.at

FAAC TUBULAR MOTORS tel. +49 30 56796645 fax +49 30 22409006 faactm.info@faacgroup.com

BENELUX

FAAC BENELUX NV/SA Brugge, Belgium tel. +32 50 320202 fax +32 50 320242 www.faacbenelux.com

FAAC TUBULAR MOTORS Schaapweg 30 NL-6063 BA Vlodrop, Netherlands tel. +31 475 406014 fax +31 475 406018 faactm.info@faacgroup.com

CHINA

FAAC SHANGHAI Shanghai, China tel. +86 21 68182970 fax +86 21 68182968 www.faacgroup.cn

FRANCE

FAAC FRANCE Saint Priest - Lyon, France tel. +33 4 72218700 fax +33 4 72218701 www.faac.fr

FAAC FRANCE - AGENCE PARIS Massy - Paris, France tel. +33 1 69191620 fax +33 1 69191621 www.faac.fr

FAAC FRANCE - DEPARTEMENT VOLETS Saint Denis de Pile - Bordeaux, France tel. +33 5 57551890 fax +33 5 57742970

GERMANY

FAAC GMBH Freilassing, Germany tel. +49 8654 49810 fax +49 8654 498125 www.faac.de

FAAC TUBULAR MOTORS tel. +49 30 56796645 fax +49 30 22409006 faactm.info@faacgroup.com www.faac.de

INDIA

FAAC INDIA PVI. LTD Noida — Delhi, India tel. +91 120 3934100/4199 fax +91 120 4212132 www.faacindia.com

IRELAND

NATIONAL AUTOMATION LTD Co. Roscommon, Ireland tel. +353 71 9663893 fax: +353 71 9663890 www.nal.ie

MIDDLE EAST

FAAC MIDDLE EAST FZE
Dubai Silicon Oasis Operation Center - Dubai, UAE
tel. + 971 4 3724190
fax+ 971 4 3724191

Headquarter & East Coast Operations FAAC International Inc. 5151 Sunbeam Road Suites 9-11 Jacksonville, Florida 32257 Tel. 866 925 3222 Toll Free Tel. 904 448 8952 Fax 904 448 8958

NORDIC REGIONS

FAAC NORDIC AB Perstorp, Sweden tel. +46 435 779500 fax +46 435 779529 www.faac.se

POLAND

FAAC POLSKA SP.ZO.0 Warszawa, Poland tel. +48 22 8141422 fax +48 22 8142024 www.faac.pl

RUSSIA

AAC RUSSIA Moscow, Russia www.faac.ru

SPAIN

F.A.A.C. SA San Sebastián de los Reyes - Madrid, Spain tel. +34 91 6613112 fax +34 91 6610050

SWITZERLAND

FAAC AG Altdorf, Switzerland tel. +41 41 8713440 fax + 41 41 8713484

UNITED KINGDOM

FAAC UK LTD.
Basingstoke - Hampshire, UK
tel. +44 1256 318100
fax +44 1256 318101
www.faac.co.uk

U.S.A.

FAAC INTERNATIONAL INC Jacksonville, FL - U.S.A. tel. +1 904 4488952 fax +1 904 4488958

FAAC INTERNATIONAL INC Fullerton, California - U.S.A. tel. +1 714 446 9800 fax +1 714 446 9898 www.faacusa.com

West Coast Operations FAAC International Inc. 357 South Acacia Avenue Unit 357 Fullerton, California 92831 Tel. 800 221 8278 Toll Free Tel. 714 446 9800 Fax 714 446 9898





FSL700 - FSW900

24VDC Commercial Vehicular Gate Operators









24VDC COMMERCIAL GATE OPERATORS: EASY INSTALLATION, FULL FEATURE, BUILT-IN BATTERY BACKUP SYSTEM

- Operates vehicular gates for high traffic and residential applications and is ideal for custom homes, apartments, self storage, and other commercial applications.
- Multi-Function battery backup is a standard feature built-in and offers main power fail and low battery control of the gate during a power failure.
- The 24VDC direct drive motor to gearbox design offers high power efficiency while reducing costs and added parts
- Built in soft start soft stop control offers a smooth, more quiet operation and is easier on the gate and gate installation.
- Simple to install design offers mulitple prewired terminals, LED indicators, installation handles, accessory shelves, and is easy to access and set limits.
- Wireless master slave is simple to install and eliminates the need for underground wire.





OPERATOR FEATURES

- · Built-in battery backup standard
- Soft Start Soft Stop smooth operation
- Heavy duty gearbox and 24VDC motor direct drive design
- Simple, clean design with less moving parts
- Fail safe design on FSL700 slide gate operator
- Release handle with optional padlock on FSW900 swing gate operator
- Zinc galvanized steel frame with handles for easy installation
- FSW900's clam shell cover can be removed without removing swing arm
- FSL700 uses a UV protected polyethelene cover with lift handle slots
- Easy access limits are simple to set
- Battery & accessory shelves

- Adjustable chain idlers for front, rear, and post mount slide gates
- Industry standard swing arm for swing gate applications
- Plug-in loop detector inputs: reverse, open, center (shadow)
- (2) AC accessory power plugs with GFCI Protection NEW ADD ON
- Built-in 3-Button control for easy setup
- Multiple terminal inputs for simple, clean wire installation
- · Maglock, solenoid, external alarm outputs
- · Power fail option can open or cycle gate
- · Low battery option can open or cycle gate
- Anti-Tailgate & Quick Close features standard
- Wireless master slave option





DIMENSIONS AND TECHNICAL CHARACTERISTICS

General	
Power input	120 VAC, 15A
Motor	24 VDC
Power	500 W, 1/2 HP
Power input fuse	5 amp FB
Accessory fuse	4 amp SLB
AC accessory outlets	2
Accessory power output	24DC
M/S wire	RS432, CAT5 wire

FSL700 Slide Gate Operator	
Gearbox	15:1 Fail Safe
Chain Size	#41, 25ft
Chain height - front mount	11" from base
Chain mount options	Front, rear, center
Travel speed	12 inches/sec
Gate capacity	1000 lbs, 40 feet
Shipping weight	125 lbs
Dimensions	22" H. 18" W. 15" D

FSW900 Swing Gate Operator		
Gearbox	900:1 Fail Secure	
Arm type	Industry standard	
Arm attachment height	17" from base	
Mounting method	Pad or baseplate	
Travel speed	90 degrees in 15 sec	
Gate capacity	800 lbs, 18 feet	
Shipping weight	150 lbs	
Dimensions	18" H, 18.5" W, 23.5" D	