

**NEW**



# SWING GATE OPERATOR

2000<sub>LBS</sub> CAPACITY



RESIDENTIAL AND COMMERCIAL  
CLASS I, CLASS II, CLASS III AND CLASS IV VEHICULAR SWING GATE OPERATOR



**New "VFlex" Control Board**

- Diagnostics, Settings, and Status Display
- Conveniently Labeled Enclosure
- Ergonomically Located

Quick Release Handle for Manual Operation

Auxiliary Output for Additional Accessories While the Gate is in Motion

**Multi-Layer Corrosion Protection:**

- G90 Galvanized
- Clear Zinc Plating
- UV Rated Powder coating
- 1/4" Steel Chassis

Conveniently Located Motor and Battery Reset Switches

Built-In Heater:  
• Cold Weather Operation Down to -20°F

Convenient Jbox for High Voltage Wiring

Removable Power Supply:  
• Convenient Fuse Access  
• L.E.D. Status Indicators  
• Convenient Power Switch  
• E-Z Access Power Outlet  
• E-Z Set-up 115V/230V  
• Included Low Voltage Option

Battery Included:  
True Battery Back-up



**COMPATIBLE WITH VIKING WIRELESS PRODUCTS**

- Wireless Master/Slave Kit provides secure and reliable wireless communication.
- Remote access to the control board settings, programming, operator diagnostics, controls, gate status and error notifications, all from the convenience of a computer or any compatible handheld device.
- Plug & Play connection for the Viking wireless expansion products.



**PROTECTION**

- Multi-Layer Corrosion Protection
  - G90 Galvanized
  - Clear Zinc Plating
  - UV Rated Powder coating
  - 1/4" Steel Chassis



**INTEGRATED HEATER**

- Built-in heater for operating temperatures down to -20°F.
- This will allow you run your operator in the coldest conditions.



**BATTERY BACKUP INCLUDED**

- Standard Battery Backup provides 400 continuous cycles at 100% duty cycle.
- With Viking's "True" Battery Backup System, batteries are not used during normal operations, maximizing battery life.



**SOLAR SMART**

- Power Saving technology minimizes current draw while at standby.



**LIGHTNING PROTECTION**

- Advanced lightning strike protection up to 20,000 volts / 10,000 amps.
- On board surge protection monitoring.



**DIAGNOSTICS DISPLAY**

- On-board LCD screen displays voltages, amps, gate status and diagnostics.

Operational Voltage	...24 VDC 1 HP
Main Power Source Options	...120 / 220 VAC Single Phase 24 AC/DC Solar Compatible
Battery	... 7 AmpHr 12 VDC x 2
Max Gate Capacity	...2000 lbs / 12' or 1200 lbs / 20'
Operating Speed	...13-16 seconds per 90°
Battery Backup	...400 full continuous duty cycles (2000lbs)
Maximum Duty Cycle	... 100% Continuous Cycle
Operating Temperature	... - 20° F to + 160° F

**WARRANTY:**  
**7 YEAR RESIDENTIAL**  
**5 YEAR COMMERCIAL**

- VIKING WIRELESS**
- SOLAR EFFICIENT OPERATION**



[www.vikingaccess.com](http://www.vikingaccess.com) • 800 908 0884