

EIS ENTRY-1

GSM Door Entry Unit



FEATURES

- Simple installation and setup
- Back lit for easy visibility
- Easy access (up to 1000 caller ID numbers)
- Up to 1000 (4 digit) entry PIN codes
- Up to 5 users per call button
- 2 relay outputs / 2 alarm inputs
- Up to 20,000 log events
- Supports 3G-GSM wireless carrier



SPECIFICATIONS


Mounting	Post or Surface
Format	Wiegand 26-bit input / output
Power supply	14.4/24 VDC 12-16 VAC
Current Consumption	
Transmitting Mode	310mA / 14 VDC
Idle Mode	240mA / 14VDC
QUAD Band GSM Module	850/900/1800/1900 MHz
FIVE Band UMTS Module	800/850/1900/2100
Unit Dimensions	11 x 7-1/2 x 2-3/8"
External Patch Antenna SMA	1
Front Plate	Grade 304 Stainless Steel
Lockable Housing	Powder coated

ACCESSORIES

EISWARE

Programming Software

Available on IOS or Android App and online at www.eisware.com.



Search:
EISWARE WEB



Optional receiver and transmitter module for wireless application



2480 South 3850 West, Suite B
Salt Lake City, UT 84120
(866) 975-0101 • (866) 975-0404 fax
www.transmittersolutions.com

All items are trademarks of their respective holders.

To have your fax number removed from future specials, please call Removal Services - 800-915-2571 ext. 47540 or fax to 866-975-0404.